

MOTOREDUKTOR: NMRV-040-71B14

WIDOK 3D



DANE TECHNICZNE I WYMIARY

GR Size	040
PAM Input PAM flange	71 B14
ACU Output hole shaft (d)	18
VB Double input shaft	NO
TFU Output flange gear unit 2	NO
DFU Output flange dimension (d)	-
PFU Output flange position	-
AL Output hole shaft (d)	NO
PAL Output shaft position	-
BR Torque arm	NO
PBR Torque arm position	-
CAP Cover	NO
TIP Motor type	T-Three phase
GRA Motor size	071
RAF Cooling	IC411-Self-Ventilated
FC Motor execution	B14
TF Break type	-
AF Brake power supply	-
COP Terminal box cover	Aluminium
CVE Fan cover	Standard
MOR Terminal box cover position	1
A	70
AC	139
B	23
B1	4
BB	6
BM	5
BM1	5
D	18(19)
D1	11

DM	14
DM1	14
E	30
F	-
FF	M5x12.5
G	70
G1	78
H	50
I	40
K	60
KE	M6x10(4)
L	71
LB	208.5
LL	238.5
M	75
N	60
N1	36.5
O	6.5
P	87
PM	105
PM1	105
Q	55
R	71.5
S	6.5
T	26
T1	12.5
TM	16.3
TM1	16
TT	20.8(21.8)
V	35
W	45°

WIDOK 2D



AKCESORIA

